

The design of the units ensures efficient use of space, which is particularly important in large cities. Easy to install and use. They support all electric vehicles and are suitable for integration with all charging service providers.

| | SAT 400 | SAT 600 | Sat Box |
|---|---------------------------------|--|---|
| Supported vehicles | Personal EV, e-deliveries | Personal EV, e-delivery, e-cars, electric buses | e-delivery, e-cars, electric buses |
| Connectors | CCS (5 m) | CCS, CCS HPC | CCS (9,5 m) |
| Maximum charging current | 400 A (up to 500 A) | CCS - 400 A (up to 500 A) CCS HPC - 500 A (up to 600 A) | 250 A |
| Number of outputs | 2× | 1× | 1× |
| Charging HUB – version with power unit | Axon Side 360, Axon Side 400 | Axon Side 400 | Axon Easy S, Axon Side, Core Charger, Mega Charger |



Satellites







SAT 400

- Ultra-fast DC charging
- LED lighting to indicate the charging point status
- Resistant construction against vandalism and temperature between -35 °C and +55 °C
- Intuitive 10" display with RFID card reader
- CMS system with up to 270° swivel arm and 4.5 m cable reach

SAT 600

- Ultra-fast DC charging
- Resistant construction against vandalism and temperature between -35 °C and +55 °C
- LED lighting to indicate the charging point status
- Remote diagnostics and system updates
- Cable management system with brake mechanism

Sat Box

- CCS connector (9.5 m)
- Column with signal lights (optional)
- Mounting column (optional)
- Cable reel (optional)
- Communication with power unit (Ethernet)
- Resistant construction against vandalism and temperature between -25 °C and +55 °C

 Compatibility with high performance power units

Saving urban space

Interoperability